

## LUPA® FENDER



308 LUPA® FENDER



## BENEFITS / FEATURES

- GOOD KNOT RETENTION
- SUPPLE SURFACE
- GREAT FOR FENDERS
- EXCELLENT SHOCK ABSORPTION
- EASY HANDLING

## APPLICATIONS

FENDER MOORING

SEE PAGE 75

## SPECIFICATIONS

|                      |                         |
|----------------------|-------------------------|
| MATERIAL             | 100% HT POLYESTER FIBER |
| SPECIFIC GRAVITY     | 1,14 KG/DM <sup>3</sup> |
| CONSTRUCTION         | 24-32 PLAITED           |
| UV RESISTANCE        | VERY GOOD               |
| CHEMICAL RESISTANCE  | GOOD                    |
| MELTING POINT        | 218°C                   |
| CRITICAL TEMPERATURE | 130°C                   |
| WORKING STRETCH      | <20%                    |
| WET ABRASION         | SUFFICIENT              |
| DRY ABRASION         | GOOD                    |
| STANDARD             | -                       |
| LENGTH               | 100-200 M ORANGE SPOOL  |

OTHER COLOURS &amp; LARGE DIAMETERS UPON REQUEST

| ART.NO | DIA | WEIGHT       | B.LOAD |
|--------|-----|--------------|--------|
|        | (Ø) | (kg / 100 m) | (kgf)* |
| 308    | 8   | 2,45         | 1.300  |
| 308    | 10  | 3,90         | 2.100  |
| 308    | 12  | 5,60         | 3.000  |
| 308    | 14  | 7,70         | 4.100  |
| 308    | 16  | 10,00        | 5.300  |
|        |     |              |        |
|        |     |              |        |

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

