

DINGHY ROCK V® MIX



KAYA ROPES

UPGRADE YOUR LINES!



121 DINGHY ROCK V® MIX


Vectran


BENEFITS / FEATURES

- GOOD PERFORMANCE IN JAMMERS
- HIGH BREAKING LOAD
- EXTREMELY LOW STRETCH
- EASY TO SPLICE

APPLICATIONS

MAIN HALYARD

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: COATED VECTRAN® FIBER
SPECIFIC GRAVITY	APPROX. 1,38 KG/DM ³
CONSTRUCTION	COVER: 20-24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
121	3	1,10	450
121	4	1,30	750
121	5	1,85	1.150
121	6	2,85	1.750
121	7	3,70	2.300

***UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)**

