

## ROCK STRONG® PLUS



# KAYA ROPES

## UPGRADE YOUR LINES!

026 - ROCK STRONG® PLUS



## BENEFITS / FEATURES

EXCELLENT BREAKING LOAD  
DURABLE  
VERY LOW STRETCH  
FIRM AND ROUND  
DOES NOT KINK

## APPLICATIONS

VESSEL PRIMARY MOORING LINES  
TUG MAIN TOW LINES  
TUG PENDANTS  
SALVAGE ROPES

## SPECIFICATIONS

MATERIAL	COVER : HT POLYESTER FIBER
	INNER COVER : -
	CORE : COATED DYNEEMA® SK 75/78
SPECIFIC GRAVITY	1,00 - 1,20 KG/DM <sup>3</sup>
CONSTRUCTION	COVER : 24 - 32 PLAITED
	CORE : 12 - 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	147°C - 256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. 0-1%
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	ISO 10325
LENGTH	UPON REQUEST

## LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT	B.LOAD *
	(Ø)	(kg / 100 m)	(kgf)
026	20	24,00	28.000
026	22	29,00	35.000
026	24	34,00	41.000
026	26	40,00	48.000
026	28	46,00	55.000
026	32	60,00	74.000
026	36	77,00	92.000
026	40	94,00	115.000
026	44	115,00	139.000
026	48	136,00	162.000
026	52	160,00	193.000
026	56	185,00	220.000
026	60	212,00	253.000
026	64	240,00	289.000
026	68	272,00	327.000
026	72	307,00	364.000
026	76	340,00	403.000
026	80	375,00	452.000
026	88	450,00	536.000
026	96	530,00	629.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)


